

Large Format Print Solutions ideal for CAD & GIS

iPF750 / iPF755

you can

The **imagePROGRAF iPF750 and iPF755** are 36"/A0 printers, delivering class leading productivity, exceptional quality, accuracy and an advanced set of features to ensure an excellent return on investment.

iPF750 / iPF755
36 INCH
2,400 X 1,200DPI
ECONOMY PRINTING MODE
5 COLOURS
A0 48 SECONDS
15,360 NOZZLES
160GB HDD (iPF755)
BORDERLESS PRINTING



Key Features

- Manage costs and track ROI - Full accounting and eMaintenance software included.
- Space saving - Unique compact design to fit anywhere.
- User Friendly - Simple roll paper loading system and control the printer from the front.
- Maximise productivity - "Hot Swap" ink tanks, changeable during production
- Minimise printer downtime with media mismatch detection (iPF755).
- High capacity basket with stacking functionality to prevent damage to prints.
- Highly accurate with 0.02mm minimum line width and +/-0.1% line accuracy.
- Integrate with your office applications with Microsoft Office Plug-in.
- HP-GL/2 and HP-RTL Compatible: -
 - Capable of handling large vector files
 - HP-GL/2 pallet and pen settings
 - HP-GL/2 and HP-RTL nesting (iPF755).
 - HP-GL/2 auto-rotation.

Specifications: iPF750 / iPF755

Class Ink Type Maximum Print Resolution Printing Speed (A0 Roll, Full Colour Image) Plain Paper Coated Paper Dimensions, Weight (Net) W x D x H (mm), (kg) Dimensions, Weight (Packaged) W x D x H (mm), (kg) Power Supply Input power Power consumption Standby power consumption (At the low power mode) 100 V - 120 V 220 V - 240V Power off (standby) Operational Environment Acoustic Noise Acoustic pressure Acoustic power Minimal Line Width Line Accuracy Operation Panel Display Large Language on operation panel Displayable Language on LCD Printer Language Interface USB Type Mode Connector type Ethernet Type Standard Protocol Operating Systems Supported Windows Macintosh Memory Standard Memory HDD	36-inch Dye and pigment reactive ink: BK, MBK x 2, C, M, Y 2,400 x 1,200 dpi 0.48 (Draft mode) 1.14 (Standard Mode) 1.14 (Draft Mode) 2.26 (Standard Mode) 3.51 (High Quality Mode) iPF750: Main unit with a basket open and a printer stand 1,304(W) x 870(D) x 1,062(H)mm ; Weight: approx. 62.9kg iPF755: Main unit with a basket open and a printer stand 1,304(W) x 870(D) x 1,062(H)mm ; Weight: approx. 63.1kg iPF750: Main unit 1,434(W) x 830(D) x 770(H)mm; Weight: approx. 75.1kg iPF755: Main unit 1,434(W) x 830(D) x 770(H)mm; Weight: approx. 75.3kg iPF750: Stand and Basket 1,380(W) x 760(D) x 240(H)mm; Weight: approx. 16.8kg iPF755: Stand and Basket 1,380(W) x 760(D) x 240(H)mm; Weight: approx. 16.8kg AC 100 - 240 V (50/60 Hz) 140W or less 5W or less 6W or less 1W or less (In compliance with Executive Order of the President of the United States of America) Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free) Operation: 50 dB (A) or less, Standby: 35 dB (A) or less Operation: 6.6 Bels or less 0.02mm (Theoretical value) ±0.1 % or less (User adjustments necessary. Printing environment media must match that used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only.) LCD: 160 x 128 dots, Key x 13, LED x 5 US-English, Japanese US-English, French, German, Italian, Spanish, Chinese (simplified), Korean, Japanese (Kanji), Russian GARO, HP-GL/2, HP RTL Built-in Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Series B (4 pins) Built-in IEEE 802.3 10base-T IEEE 802.3u 100base-TX / Auto-Negotiation IEEE 802.3ab 100base-T / Auto-Negotiation IEEE 802.3 x Full Duplex IPX/SPX (Netware 4.2(J), 5.1(J), 6.0(J)) SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk 2000 (32)/XP (32 & 64)/Server 2003 (32 & 64)/Server 2008 (32 & 64)/Vista (32 & 64) OS X (32 & 64) 256Mb iPF755 - 160Gb (including 8Gb Dynamic Memory)
PRINT HEAD Model Type Head configuration Nozzle pitch Nozzle per chip Droplet size Head replacement	PF-04 Bubble-jet on demand 6 colours integrated type (6 chips per print head x 1 print head) 1,200dpi MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each 4 pl per colour User replacement

INK TANK Model	PFI-102 (130ml): MBK/BK/C/Y, PFI-104 (130ml): M
MEDIA HANDLING Roll paper Cut sheet Media type Roll paper	One roll, top-loading, front output Top-feeding, front output (Manual feed using media locking lever) Standard Paper 80gsm Standard Paper 90gsm Matt Coated Paper 90gsm Glossy Photo Quality Paper 190gsm / 240gsm / 300gsm Satin Photo Quality Paper 190gsm / 240gsm / 300gsm Pearl Photo Paper 260gsm Matt Coated Paper 120gsm / 140gsm / 180gsm Opaque White Paper 120gsm High Resolution Self-adhesive Graphic Paper 140gsm High Resolution Barrier Paper 180gsm Glossy Proofing Paper 195gsm Semi-Glossy Proofing Paper 195gsm / 255gsm
Media Size Roll paper (width)	ISO: A3, A2, A2+, A1, A0, JIS: B4, B2, B1, ARCH: 24", 30", 36" Others: 10", 14", 16", 17", Banner (300mm)
Cut sheet	ISO: A4, A3, A3+, A2, A2+, A1, A0, B4, B3, B2, B1 DIN: C4, C3, C2, C1, C0 JIS: B4, B3, B2, B1, B0 ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", 28 x 40", 34 x 44" ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", 26 x 38", 27 x 39", 30 x 42", 36 x 48" Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15" 16 x 20" (US Photo size), Poster: 20 x 30", 30 x 40", 300 x 900mm, Others: 13 x 22" Roll paper & Cut sheet: 0.07 - 0.8mm
Media Thickness Maximum Outside Diameter of Roll Paper Media Core Size Media Width	150.0mm Internal diameter of roll core: 2" / 3" Roll paper: 254 (10") - 914.4 (36")mm Cut sheet: 203.2 (8") - 917 (DIN C0)mm
Minimum regular format size (Vertical)	Roll paper: 203.2mm (8") Cut Sheet: 279.4mm (11"): Letter size (long side)
Maximum Printable Paper Length	Roll paper: 18m (Varies according to the OS and application) Cut sheet: 1.6m (Varies according to the OS and application)
Margins (Top, Bottom, Sides) Recommended area	Roll paper: Top: 20mm, Bottom: 5mm, Side: 5mm Cut sheet: Top: 20mm, Bottom: 23mm, Side: 5mm
Printable area	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless print): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet: Top: 3mm, Bottom: 23mm, Side: 3mm
Media width for borderless printing	10"(254mm), B4(257mm), A3(297mm), Banner(300mm), 14"(356mm), A2(420mm), A2+/17"(432mm), B2(515mm) A1(594mm), 24"(610mm), B1 (728mm), A0(841mm), 36" (914mm)
OPTION Roll Holder Set (for both 2" and 3" core roll media)	RH2-33
CONSUMABLES Ink Tank Print Head Maintenance Cartridge	PFI-102 (130ml): MBK/BK/C/Y, PFI-104 (130ml): M PF-04 MC-10
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



Canon Inc.
canon.com
Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V., 2011

Canon (UK) Ltd
Woodhatch
Reigate, Surrey
RH2 8BF
Tel: 01737 220000
Fax: 01737 220022
www.canon.co.uk

Canon Ireland
Arena Road, Sandyford
Industrial Estate
Dublin 18, Ireland
Tel: 01 2052400
Fax: 01 2958141
www.canon.ie